



LCD Médical AG-17RD

A durable, versatile, high performance display with an array of built-in video options designed expressly for medical environments.



The AG-17RD is a durable, high resolution 1280 x 1024, 17" display featuring the specified DC 24 V medical power supply essential for medical applications. A sturdy metal casing and VESA compliant design allows for a variety of mounting possibilities. The protection of NeoV™ Optical Glass and the flexibility of analogue, DVI, S-Video and CVBS inputs make the AG-17RD perfect for patient education in medical environments.



NeoV™ Optical Glass - The most trusted hard glass protection available.



EN 60601-1
IEC 60601-1



- > SXGA 1280 x 1024 resolution
- > NeoV™ Optical Glass
- > Durable metal casing
- > Swift 3 ms response time
- > High 3000:1 dynamic contrast ratio
- > S-Video and CVBS inputs
- > DC 24 V medical power supply
- > EN60601-1 medical certification
- > Equipotential Terminal safety standard
- > Optional handle allows for easy movement of display
- > Auto-adjustment for optimal settings
- > Kensington® security socket
- > VESA standard mount

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.ancelgenesys.fr>



LCD Médical AG-17RD

Specifications

Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432 mm) SXGA 1280 x 1024
	Max.	0,264 mm
	Resolution	300 cd/m ² (Typical)
	Pixel Pitch	3000:1 (DCR)
	Brightness	160°/160° (Typical)
	Contrast Ratio	16.2M
	Viewing Angle (H/V)	3 ms (GTG)
	Display Colour	50,000hrs (Minimum)
Frequency (H/V)		H: 30 kHz - 80 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video	4-Pin Mini Din S-Video
	CVBS	CVBS Jack
Power	AC-DC Adaptor	External
	Power	AC 100 - 240 V, 50 - 60 Hz
	Consumption	< 48 W (On) < 5 W (Stand-by) < 2 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.18")
	Reflection Rate	< 1%
	Transmission	> 96%
	Rate Hardness	> 6H (MOH's Rating)
Plug & Play	VESA	DCC 2B, DDC/CI
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPM/PMI	Yes (100 - mm)
Tilt	Tilt	0° ~ +15°
Dimensions	Product (W x H x D)	408 x 398 x 175 mm (16.1" x 15.7" x 6.9")
	Packaging (W x H x D)	493 x 513 x 226 mm (19.4" x 20.2" x 8.9")
Weight	Product Weight	w/ Base 6.8 kg (13.9 lbs) w/o Base 6.1 kg (13.4lbs)
	Packaged Product Weight	10,0 kg (22.0 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, ISO13406-2, GOST-R, NOM, FCC, CE, BSMI, WEEE, RoHS EN60601-1
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), 15-Pin - D-Sub cable, 24-Pin DVI cable, S-Video cable, CVBS cable, AC power cord 1.8 m, DC power cord 5 m, power adaptor
	Optional	Display handle, display base

AG-17RD



Strong metal design for increased durability



Analogue, DVI, S-Video and CVBS inputs for any video device or PC data feeds



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Convenient handle allows for easy movement

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelgenesys.fr>