



# Imprimante Jet D'Encre Durcie A4 AG-800

MIL-STD-810E / MIL-STD-461E / RS105



The AG-800 Printer is housed in a unique custom made aluminium rugged enclosure providing instant access to the printer consumables and ease of maintenance.

With the capability to print in both monochrome and colour, this rugged printer offers efficient high volume printing (up to 21 pages per minute) whilst providing high performance 4800 x 1200 dpi resolution.

This AG-800 printer is suitable for a range of applications, offering the durability and resilience to survive extreme military and commercial conditions, meeting MIL-STD-810E, MIL-STD-461E and RS105. Designed to withstand hostile environments in mobile or fixed applications, the printer is fully compatible with any computer.

This rugged printer is available in either direct to desk mount, 19" rack mount or quick release vehicle mounting options.

## FEATURES INCLUDE:

- MIL-STD-810E
- MIL-STD-461E & RS105
- MIL-STD-1275B
- A range of mounting options
- Rugged Design
- Aluminium alloy rugged enclosure
- Up to 4800 dpi resolution printing
- Full colour A4 high speed printing
- Field deployable / Man portable

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelgenesys.fr>



# Imprimante Jet D'Encre Durcie A4 AG-800

## TECHNICAL SPECIFICATION

<b>COTS EQUIPMENT</b>	HP Scanning Imager 800
<b>TECHNOLOGY</b>	Inkjet
<b>CASE MATERIAL</b>	Aluminium Alloy
<b>DIMENSIONS</b>	290mm(H) x 474mm (W) x 535mm (D)
<b>WEIGHT</b>	25Kg (30Kg with IKEE + AKEE)
<b>PERFORMANCE</b>	Up to 21 pages per minute
<b>RESOLUTION</b>	Monochrome up to 1200 x 1200 dpi Colour up to 4800 x 1200 dpi
<b>SCANNING PRINT ZONE</b>	8.5 inches
<b>MEMORY</b>	8MB as standard
<b>PAPER HANDLING</b>	A4, A5, B5 cut sheet
<b>COMPATIBILITY</b>	Microsoft Windows 2000 / XP
<b>EMULATIONS</b>	HP PCL Level 3 Enhanced
<b>INTERFACE</b>	Circular MIL SPEC Connectors AC/DC Power USB 1.1 Ethernet with Server Parallel IEEE 1284 D-Sub
<b>POWER SUPPLY</b>	85-265 V AC (50/60 Hz) 19-32 V DC
<b>POWER CONSUMPTION</b>	60 Watts max
<b>COLOUR</b>	Infra-Red Reflective Matt Green in accordance with DEF STAN 03-32 & 00-23
<b>MTBF</b>	11,000 hours
<b>MTTR</b>	<30 minutes
<b>DECONTAMINATIONS</b>	Exposure to in-service decontaminants: Fullers Earth, Super Tropical Bleach and decontamination Chemical Agent without degradation of performance or damage to external surface.
<b>LOW TEMPERATURE</b>	<b>OPERATING</b> MIL-STD-810E, Method 502.3, Procedure II, -18°C <b>STORAGE</b> MIL-STD-810E, Method 502.3, Procedure I, -34°C
<b>HIGH TEMPERATURE</b>	<b>OPERATING</b> MIL-STD-810E, Method 501.3, Procedure II, +50°C <b>STORAGE</b> MIL-STD-810E, Method 501.3, Procedure I, +55°C
<b>RELATIVE HUMIDITY</b>	MIL-STD-810E, Method 507.3, Procedure III, 5% - 95%
<b>SHOCK OPERATION</b>	MIL-STD-810E, Method 516.4, Procedure I, 20g/11ms half sine
<b>DROP</b>	MIL-STD-810E, Method 516.4, Procedure IV
<b>RAIN</b>	DEF STAN 07-55, Test D3 Duration B
<b>SAND AND DUST</b>	MIL-STD-810E, Method 510.3, Procedure I and II
<b>SALT CORROSION</b>	MIL-STD-810E, Method 509.3, Procedure I, Notice 1
<b>ATMOSPHERIC PRESSURE</b>	MIL-STD-810E, Method 500.3, Procedure I 15000 feet
<b>FUNGAL GROWTH</b>	MIL-STD-810E, Method 508.4, Procedure I

<b>TRANSPORTATION SURVIVAL</b>	MIL-STD-810E, Method 514.4, Procedure III, Loose Cargo
<b>VIBRATION</b>	MIL-STD-810E, Method 514.4, Procedure I, Category 8
<b>EMC</b>	MIL-STD-461E Army Ground Equipment CE102, CS101, CS114, CS115, CS116, RE102, RE103
<b>TEMPEST</b>	Optional
<b>PRODUCT SAFETY</b>	EN 60950
<b>ELECTROSTATIC DISCHARGE</b>	EN 61000-4-2
<b>NEMP</b>	MIL-STD-461E, RS105
<b>POWER COMPATIBILITY</b>	MIL-STD-1275B
<b>PRODUCT VARIANTS</b>	<ul style="list-style-type: none"> <li>• Feet and Handles</li> <li>• Rack Mounted</li> <li>• Vehicle Installation IKEE</li> </ul>
<b>COLOURS</b>	NATO Green as standard Other colours and finishes available on request



Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelgenesys.fr>