



LCD Industriel IP65 (face avant) AG-H6504S

IP65 Front, Chassis, 65" LCD, 1920x1080

Specification



Features

- IP65 front side sealed for water-dust proof
- Optional panel with ultra high brightness and super dynamic contrast, along option with auto-brightness sensor offers application in day and night.
- Optional to built-in touch screen for interactive application.

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 65" viewable diagonal area	
	Active Area / Pixel Pitch	1428.48(H) x 803.52(V) mm / 0.744(H) x 0.744(V) mm	
	Native Resolution / Colors	1920(H) x 1080(V) / 16.7 Million	
	Brightness / Contrast	550 cd/m ² (typ) / 2000: 1	
	Response Time	≤6 ms (G-to-G)	
	Viewing Angle (typical)	H. 176° (-88°~+88°) - +. V. 176°(-88°~+88°)	
	Light Source	CCFL, Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal Analog RGB (0.7/1.0 v _{pp} , 75 ohms)	
		Sync Separate Sync, Composite Sync, Sync On Green	
		Frequency F _H : 30 - 82Khz, F _v : 50 - 75Hz	
	Audio System	3W Amplifier	
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x AC Inlet		
Convenient Features	IP65 front side sealed for water-dust proof		
	Auto Calibration, Back Light Adjustment, Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages, Wall Mount Ready (VESA 600 x 400 mm)		
Power	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	630 watt, < 5 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C - 50°C (32°F - 122°F) , 10% - 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C - 60°C (- 4°F - 140°F) , 10% - 90% (no condensation)	
Certification	FCC, CE		
Dimensions	Physical	With Base(W xHx D) : TBD	
		Without Base(W xHx D): TBD	
	Carton	WxHxD = TBD	
Weight	NW. / GW.	38.0 Kgs / 41.0 Kgs	
Options	Touch	Video / TV	Enhanced Panel
	Resistive touch	SV + AV	Panel with LED backlight
	Capacitive touch	SV + AV + AV Looping	High brightness panel
	SAW touch	SV + AV + TV	Wide Temperature
	Infrared touch		Sunlight Readable
	Protected glass		Auto-Dimming
			Others
			Digital Signage(Stand alone)
			Networking Digital Signage
			Motion Sensor
			Light Sensor

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelegenesys.fr>