



Imprimante Portable AG-P1300

Compact and stylish

- Unique SINGLE-handed easy paper-load system – no other printer is easier!
- Utilising a high speed and high quality fixed head thermal mechanism with superb quality text.
- Choice of interface solutions including Serial RS232, *full implementation* IrDA® and Bluetooth®.
- Strong case design that won't stress the lid hinge.
- Miniature size - yet takes up to 16m paper roll.
- Choice of battery management within one printer (re-chargeable within the unit or use primary cells). Invehicle solutions and mains supply also available.



Typical Applications include:

Mobile ticketing and recording.
Use with PDA's. Queue busting.
Utility billing.
In-vehicle receipting.
Financial transactions.
Taxi receipt printing.
Law enforcement agencies.
Test and measurement.
Medical.

Design registered. Bluetooth certification pending.

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acegenesys.fr>



Imprimante Portable AG-P1300

Specification	AG-P1300	AG-P1300-IR	AG-P1300-BT
Data Input	RS-232 Serial (RJ12 connector)	RS-232 Serial (RJ12 connector)	RS-232 Serial (RJ12 connector)
Wireless Data Input	N/A	IrDA (IrPHY V1.0, IrLAP, IrLMP, IAS, TinyTP, IrCOMM 9-wire)	Bluetooth
Print Method	Fixed head thermal mechanism (Fujitsu FTP-628MCL103)		
Print Speed	60 mm/s (at 7.2V battery voltage); 50mm/s (typical)		
Paper Specification	Paper Roll Width: 57.5 ± 0.5mm. Max roll diameter: 36mm (Length: 14.5 - 16 meters) Accepts paper rolls with or without a core		
Print Width	48 mm		
Dots per line (graphics)	384		
Dot spacing	8 dots/mm (vertical and horizontal)		
Sensors	Paper Out (Opto reflective) and Head Up (Mechanical)		
Data Buffer	20 Kb		
Baud Rate	For serial RS232 only: Up to 57,600 (9600 Default)		
Character Set	IBM® 224 character set, CP437. (See note 1)		
Number of columns	12, 16, 21, 24, 42, 32 (Default). (See note 1)		
Font (dots)	7 x 24, 10 x 24 (Default). (See note 1)		
Dimensions	47 x 92 x 108 mm (H x W x L)		
Weight	330g (including battery and full roll of paper)		
Power Supply Options	<p>As standard the AG-P1300 range is supplied with a shrink-wrapped re-chargeable battery pack (5 cell 6V NiMH), together with an adapter to allow the use of primary cells. Note that chargers and data or power cables need to be ordered separately (see below) or as part of a complete kit. Power supply options include:</p> <ul style="list-style-type: none"> • AG-C1300: Universal i/p trickle charger • AG-C1300B: British trickle charger • AG-C1300FC: Universal i/p combined fast charger and 12V vehicle charger 		
Other options	<ul style="list-style-type: none"> • AG-P1300BR-01: Combined wall mounting bracket and belt clip • AG-P1300-D9: D9 to RJ12 data cable (with jack socket for alternative charging) • AG-P1300BP-01: Spare NiMH battery pack 		
Windows® Driver	Win98, WinME, WinNT, Win2k, WinXP.		
Temperature Range (operating)	0 - 50°C		
Reliability - MCBF	10 ⁸ print pulses or 50kms. >13 million print lines (Approx. 3,500 paper rolls).		

Note 1: The proprietary Font Editor Utility software (order code Ap800FEU) enables customisation of character fonts by the user.

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelgenesys.fr>