



AG-PDA500B

- Functionality

AG-PDA500B is the AutoID PDA integrated with Barcode Scanner as well as Voice and Data Communication and WLAN. The ability to collect barcode data and transfer data with high-speed in a single device improves field force automation and increases productivity.

- Rugged

AG-PDA500B is built to withstand harsh work environments.

- Rated IP-65 for protection against rain and dust
- Withstand multiple 1.5m drops to steel surface
- Operate in a temperature range of -20°C to 55°C

- Compatibility

AG-PDA500B with Windows Mobile-based operating system makes it easy to install custom applications and access to your work PC. The device allows you to manage real-time information all about work documents, customers, inventory, delivery and much more without any restraints of time or place.

- Ergonomic

- 3.5" display delivers excellent graphic capability and readability.
- Touch screen and numeric keypad provides simple and easy operation.
- Sleek, compact and hand-held device grants you easy control of your work with one hand on the go.
- Rugged AutoID PDA
- IP-65
- Barcode Scanner Integrated
- GSM/GPRS/EDGE or CDMA 1x/EvDO
- WiFi (802.11a/b/g)
- Windows Mobile 5.0, Windows Mobile 6.0 or Windows CE 5.0
- 128MB RAM 128MB ROM
- Bluetooth, 2 Megapixel Camera Integrated



Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acegenesys.fr>



AG-PDA500B

Product	AG-PDA500B
Physical Characteristics	
Dimensions (W x H x D)	75 x 150.3 x 24.9mm / 3.0 x 5.9 x 1.0 inch
Weight	Excluding battery: 253g / Including standard battery: 314g / Including extened battery: 347g
Display	3.5" QVGA with backlight, TFT-LCD, 260K, 240 x 320
Touch Panel	Analog resistance type
Keypad	Numeric keypad
Standard Battery	Rechargeable, 3.7V, 2,300mAh, Li-ion
Extended Battery (optional)	Rechargeable, 3.7V, 3,700mAh, Li-ion
Expansion Slot	Customer-accessible MiniSD slot for removable memory card up to 2G
SIM Slot	1 SIM
Audio	Speaker, Headset jack
Camera	2 megapixel color camera with LED flash / Ultra bright LED flash (optional)
GPS	Integrated GPS with Network Independent A-GPS
Performance Characteristics	
CPU	PXA 320, 806MHz
OS	Windows Mobile 6.1
Memory	128MB RAM / 256MB ROM
Interface	RS-232C, USB 1.1 Host & Client, Ethernet via cradle
User Environment Characteristics	
Operating Temp	-20°C to 55°C / -4°F to 131°F
Storage Temp	-25°C to 70°C / -13°F to 158°F
Humidity	93% non-condensing
Drop Spec	5ft. / 1.5m drop to steel surface, 2drops per 6 sides
Rain/Dust Protection	IP65
Integrated Radio	
WWAN Radio	GSM / GPRS / eGPRS (850, 900, 1800, 1900 MHz)
WLAN Radio	IEEE 802.11b/g
WPAN Radio	Bluetooth Class II V2.0+EDR, IrDA 1.2
Data Capture	
Barcode Scanner	1D&PDF417 Laser Class II or 1D&2D CMOS Imager

Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS SA.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.ancelgenesys.fr>