



## AG-PDA600RF

### - Ultimate Form Factor

AG-PDA600RF allows working without any restraints of harsh work environment. It meets IP65 sealing requirements, withstands 12 drops at 1.8m to steel surface and operates in a temperature range of -20°C to 55°C. In addition, powerful 4,400mAh battery ensures continuous operation for a full day.

### - Revolutionary Integration

AG-PDA600RF gives an ability to manage more data faster. Integrated RFID Reader and 1D/2D Barcode Scanner enable versatile data capture in a single device. Moreover, 3.0 megapixel autofocus camera with flash supports snapping sharper images from a short distance and under dim light.

### - Latest Technologies

AG-PDA600RF features the full range of latest technologies. 806MHz processor and Windows Mobile 6.1 operating system deliver maximum computing power with easy operation and system integration capability. It supports large memory capacity with 256MB RAM 512MB ROM and MicroSD slot.

### - Flexible Communications

AG-PDA600RF provides accuracy and speed data capability for improving work efficiency and flexibility. HSDPA, WiFi and Bluetooth enable real-time communications between mobile workers and head office. An integrated A-GPS allows tracking user position and streamlining rout plan.

### - Outstanding Ergonomics

The large 3.5 VGA display gives visual and tactile enhancement. Moreover, the crack-resistant TouchWindow LCD supports substantial protection for the touch sensitive display. Additionally, Numeric/QWERTY keypad with backlight enables easy and precise typing in any light level.

- Powerful AutoID PDA
- IP65
- Barcode Scanner, RFID Reader Integrated
- HSDPA/GSM
- WiFi (802.11b/g)
- Windows Mobile 6.1 or Windows CE 6.0
- 256 RAM 512 ROM
- Bluetooth, 3 Megapixel Camera Integrated



Photos non contractuelles

Les spécifications sont données à titre indicatif ; elles sont susceptibles d'être modifiées sans préavis.

Toutes les marques citées sont déposées par leurs propriétaires respectifs.

ACEL GENESYS S.A.S. – Z.A. – 1, route de Galluis – 78940 La Queue Lez Yvelines

Tél : 01.34.86.45.56 – Fax : 01.34.86.42.83 – <http://www.acelgenesys.fr>



# AG-PDA600RF

## Physical Characteristics

<b>Dimensions (W x H x D)</b>	80 x 160 x 35.5mm / 3.1 x 6.9 x 1.4 inch
<b>Weight</b>	Including battery: 407g
<b>Display</b>	3.5" VGA with backlight, TFT TouchWindow LCD, 260K, 480 x 640 3.5" QVGA with backlight, TFT TouchWindow LCD, 260K, 240 x 320
<b>Touch Panel</b>	Analog resistance type
<b>Keypad</b>	Numeric / QWERTY
<b>Battery</b>	Rechargeable, 3.7V, 4,400mAh, Li-ion
<b>Expansion Slot</b>	Customer-accessible MicroSD slot for removable memory card up to 8G
<b>SIM/SAM Slot</b>	1SIM / 1SAM
<b>Audio</b>	High Volume speakers, Headset jack
<b>Camera</b>	3 megapixel autofocus camera with LED flash
<b>GPS</b>	Integrated GPS with Network Independent A-GPS

## Performance Characteristics

<b>CPU</b>	PXA 320, 806MHz
<b>OS</b>	Windows Mobile 6.1 / Windows CE 6.0
<b>Memory</b>	256MB RAM / 512MB ROM
<b>Interface</b>	RS-232C, USB 2.0(full-speed) Host & Client, Ethernet via cradle

## User Environment Characteristics

<b>Operating Temp</b>	-30°C to 60°C / -22°F to 140°F, MIL-STD 810F, Method 501.4, Procedure II, Method 502.4, Procedure I,II&III
<b>Storage Temp</b>	-40°C to 70°C / -40°F to 158°F, MIL-STD 810F, Method 501.4, Procedure I, Method 502.4, Procedure I,II&III
<b>Temp Shock</b>	MIL-STD 810F, Method 503.4, Procedure I (-35°C/65°C)
<b>Humidity</b>	MIL-STD 810F, Method 507.4, 90%RH temp cycle 0°C/70°C
<b>Drop</b>	6ft. / 1.8m drop to steel surface, 2 drops per 6 sides; meets and exceeds MIL-STD 810F
<b>Sand and Dust</b>	IP65, MIL-STD 810F, Method 510.4, Procedures I&II, KWF-test certified
<b>Water</b>	IP65, MIL-STD 810F, Method 516.5, Procedure IV, KWF-test certified
<b>Vibration</b>	MIL-STD 810F, Method 514.5, Procedure I&II
<b>Altitude</b>	MIL-STD 810F, Method 500.4, Procedure I,II&III, 15,000 ft at 23°C/73°F

## Integrated Radio

<b>WWAN Radio</b>	GSM / HSDPA (850, 900, 1800, 1900, 2100 MHz)
<b>WLAN Radio</b>	IEEE 802.11b/g
<b>WPAN Radio</b>	Bluetooth Class II V2.0+EDR, IrDA 1.2

## Data Capture

<b>Barcode Scanner</b>	1D&PDF417 Laser Class II or 1D&2D CMOS Imager
<b>RFID Reader</b>	Integrated RFID, ISO 14443 A/B (MIFARE, Calypso), ISO 15693