



# E-W22



## ▶ FEATURES

- 22" widescreen format
- WSXGA+ 1680 x 1050 resolution
- NeoV Optical Glass™
- Exquisitely elegant exterior
- Stylish rear side design
- Swift 3ms response time
- Crisp 2000 contrast ratio
- High 300 brightness
- Dual digital and analog inputs
- Built-in HDCP for HD-format video
- 1080p support
- Built-in speakers with headphone jack
- Auto-adjustment for optimal settings
- Hot key for preferable video mode: User, Text, Movie, Game, and Graphic
- Kensington® security socket
- VESA standard wall mount

## ▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	22.0" (559mm)
	<b>Max. Resolution</b>	WSXGA+ 1680 x 1050
	<b>Pixel Pitch</b>	0.282mm
	<b>Brightness</b>	300cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	2000:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	170°/160° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time</b>	3ms (GTG)
Frequency (H/V)	H:	24kHz - 83kHz
	V:	50Hz - 76Hz
<b>Max. Pixel Clock</b>	160 MHz	
<b>Life Time</b>	50,000hrs (Minimum)	
Input	<b>Analog</b>	15-Pin D-Sub
	<b>Digital</b>	24-Pin DVI-D
Audio	<b>Audio In</b>	3.5mm Audio Line-in
	<b>Audio Out</b>	3.5mm Headphone Jack
	<b>Speaker</b>	2W x 2
Connector	<b>Power</b>	3-Pin AC Plug
NeoV Optical Glass	<b>Thickness</b>	3.0mm (0.18")
	<b>Reflection Rate</b>	<1%
	<b>Transmission Rate</b>	>96%
	<b>Hardness</b>	>6H (MOH's Rating)
Tilt	<b>Tilt</b>	+5° ~ +25°
Mounting	<b>VESA FPMPI</b>	Yes (100mm)
Regulation Approval	<b>Certifications &amp; Compliance</b>	UL/CUL, FCC, NOM, CB, CE, TUV/Baurt, NORDIC, BSMI, EPA, GOST-R/HYGIENIC, WEEE, RoHS
	<b>VESA</b>	DDC-2B, DDC-CI
Power	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz
		<55W (On)
		<2W (Stand-by) <1W (Off)
Dimensions	<b>Net (W x H x D)</b>	512 x 416 x 196 mm (20.1" x 16.4" x 7.7")
	<b>Packing (W x H x D)</b>	594 x 564 x 204 mm (23.4" x 22.2" x 8.0")
Weight	<b>Net Weight</b>	7.9 kg (17.4 lbs)
	<b>Gross Weight</b>	9.0 kg (19.8 lbs)
Packing	<b>1 Pallet</b>	40 Sets
	<b>20' Container</b>	320 Sets
	<b>40' Container</b>	720 Sets

All specifications are subject to change without prior notice

