

# TS-15S (S15T) tactile



## LES AVANTAGES

- Design élégant et ultra plat
- Temps de réponse 12ms
- Rapport de contraste 500 : 1
- Luminosité 400cd/m<sup>2</sup> pour des couleurs plus vivantes
- Technologie ELO TouchScreen Serial
- Interface RS232
- Dalle à technologie capacitive
- Onde de surface
- Entrée VGA
- Ajustement automatique des paramètres
- Compatible Kensington®
- Compatible VESA
- Câbles fournis : VGA, RS232



## SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD
	<b>Panel Size</b>	15.0" (381mm)
	<b>Max. Resolution</b>	XGA 1024 x 768
	<b>Pixel Pitch</b>	0.267mm
	<b>Brightness</b>	400cd/m <sup>2</sup> (Typical)
	<b>Contrast Ratio</b>	500:1 (Typical)
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment
	<b>Viewing Angle (H/V)</b>	130°/110° (Typical)
	<b>Display Color</b>	16.7M
	<b>Response Time (R/F)</b>	15ms/10ms (Typical)
Input	<b>Frequency (H/V)</b>	H: 30kHz - 60kHz V: 50kHz - 75kHz
	<b>Max. Pixel Clock</b>	80MHz
Connector	<b>Life Time</b>	50,000hrs (Minimum)
	<b>Touch Interface</b>	8-Pin Mini Dim
Touch	<b>Analog</b>	15-Pin D-Sub
	<b>Power</b>	3-Pin AC Plug
Screen	<b>Technology</b>	SAW (Surface Acoustic Wave)
	<b>Optical Transmission</b>	>90%
	<b>Positional Accuracy</b>	<1% Deviation Error
	<b>Panel Resolution</b>	4096 x 4096
	<b>Active Force</b>	<3 ounces
	<b>Panel Interface</b>	RS-232 or USB
	<b>Glass Thickness</b>	0.118/3.0mm
	<b>Life Performance</b>	50 million touches at a single point
	<b>Operational Temp.</b>	-20°C to 50°C
	<b>Storage Temp.</b>	-40°C to 71°C
Tilt	<b>Humidity</b>	90% RH at 40°C
	<b>Tilt</b>	+10°
Mounting	<b>VESA FPMPMI</b>	Yes (75mm)
Regulation Approval	<b>Safety &amp; EMI</b>	UL/CUL, TUV/GS, NORDIC, CB, TCO 99, FCC, CE, GOST, ISO 13406
	<b>VESA</b>	DDC 1/2B, DPMS
Power	<b>Power AC</b>	100 - 240V, 50 - 60Hz
	<b>Consumption</b>	<40W (On) <5W (Stand-by) <5W (Off)
	<b>Dimensions</b>	<b>Net (W x H x D)</b> 386 x 360 x 169mm (17.0" x 16.0" x 6.7") <b>Packing (W x H x D)</b> 475 x 480 x 210mm (48.7" x 18.9" x 8.3")
Weight	<b>Net Weight</b>	5.5Kg (12.1lbs)
	<b>Gross Weight</b>	7.5Kg (16.5lbs)
Packing	<b>1 Pallet</b>	40 Cartons
	<b>20' Container</b>	480 Sets
	<b>40' Container</b>	960 Sets

All specifications are subject to change without prior notice.



Acel Genesys  
Za - 1, route de Galluis  
78940 La Queue Lez Yvelines

Tel : 01.34.86.45.56  
Fax : 01.34.86.42.83

<http://www.acelgenesys.fr>