

# TS-17R (S17T) Tactile



## LES AVANTAGES

- Design élégant et ultra plat
- Temps de réponse 4ms
- Rapport de contraste 500 : 1
- Luminosité 300cd/m<sup>2</sup> pour des couleurs plus vivantes
- Technologie ELO TouchScreen Serial
- Interface RS232
- Dalle à technologie résistive 5 fils
- Entrée VGA
- Ajustement automatique des paramètres
- Compatible Kensington®
- Compatible VESA
- Câbles fournis : VGA, RS232



## SPECIFICATION

|                     |                             |   |
|---------------------|-----------------------------|---|
| Panel               | <b>Panel Type</b>           | TFT LCD   |
|                     | <b>Panel Size</b>           | 17.0" (432mm)   |
|                     | <b>Max. Resolution</b>      | SXGA 1280 x 1024  |
|                     | <b>Pixel Pitch</b>          | 0.264mm   |
|                     | <b>Brightness</b>           | 300cd/m <sup>2</sup> (Typical)  |
|                     | <b>Contrast Ratio</b>       | 500:1 (Typical)   |
|                     | <b>Surface Treatments</b>   | Hard Coating (3H), Anti-glare Treatment   |
|                     | <b>Viewing Angle (H/V)</b>  | 140°/130° (Typical)   |
|                     | <b>Display Color</b>        | 16.7M   |
|                     | <b>Response Time</b>        | 4ms (GTG)   |
|                     | <b>Frequency (H/V)</b>      | H: 31kHz – 82kHz<br>V: 50Hz – 75Hz  |
|                     | <b>Max. Pixel Clock</b>     | 135 MHz   |
| Input               | <b>Life Time</b>            | 50,000hrs (Typical)   |
|                     | <b>Touch Interface</b>      | 8-Pin Mini Dim  |
|                     | <b>Analog</b>               | 15-Pin D-Sub  |
| Connector           | <b>Digital</b>              | 29-Pin DVI-D  |
|                     | <b>Power</b>                | DC+12V  |
| Touch Screen        | <b>Technology</b>           | 5-wire Resistive  |
|                     | <b>Optical Transmission</b> | >80%  |
|                     | <b>Positional Accuracy</b>  | <1% within precision area   |
|                     | <b>Active Force</b>         | 300 g   |
|                     | <b>Panel Interface</b>      | RS-232  |
|                     | <b>Glass Thickness</b>      | 2.1mm   |
|                     | <b>Life Performance</b>     | 35 million hits (finger)<br>100,000 characters input (pen)  |
|                     | <b>Operational Temp.</b>    | -20°C to 70°C   |
|                     | <b>Storage Temp.</b>        | -40°C to 80°C   |
|                     | <b>Humidity</b>             | Operating: <90%RH from -20°C to 60°C<br>Operating: 133.8 g/m <sup>3</sup> , if >60°C<br>Storage: <95%RH from -20°C to 60°C<br>Storage: 142.9g/m <sup>3</sup> , if >60°C |
| Tilt                | <b>Tilt</b>                 | +5°   |
| Mounting            | <b>VESA FPMPMI</b>          | Yes (100mm)   |
| Regulation Approval | <b>Safety &amp; EMI</b>     | UL/CUL, TUV/ GS, CB, FCC, CE  |
| Power               | <b>VESA</b>                 | DDC /CI, DPMS, DDC2B  |
|                     | <b>Power AC Consumption</b> | 100 - 240V, 50 - 60Hz<br><35W (On)<br><2W (Stand-by)<br><1W (Off)   |
| Dimensions          | <b>Net (W x H x D)</b>      | 436 X 427 X 200 mm<br>(17.2" x 16.8" x 7.9")  |
|                     | <b>Packing (W x H x D)</b>  | 525 x 550 x 175 mm<br>(20.7" x 21.7" x 6.9")  |
| Weight              | <b>Net Weight</b>           | 7.5 Kg (16.52lbs)   |
|                     | <b>Gross Weight</b>         | 10Kg (22 lb)  |
| Packing             | <b>1 Pallet</b>             | 36 Cartons  |
|                     | <b>20' Container</b>        | 360 Sets  |
|                     | <b>40' Container</b>        | 720 Sets  |

All specifications are subject to change without prior notice



Acel Genesys  
ZA - 1, route de Galluis  
78940 La Queue Lez Yvelines

Tel : 01.34.86.45.56  
Fax : 01.34.86.42.83

<http://www.acelgenesys.fr>