

# X-15



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 8ms response time
- High 400 brightness
- Crisp 500 contrast ratio
- DVI ready for high quality signal
- S-Video\* and CVBS\* inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white

▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD	
	<b>Panel Size</b>	15.0" (381mm)	
	<b>Max. Resolution</b>	XGA 1024 x 768	
	<b>Pixel Pitch</b>	0.297mm	
	<b>Brightness</b>	400cd/m <sup>2</sup> (Typical)	
	<b>Contrast Ratio</b>	500:1 (Typical)	
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment	
	<b>Viewing Angle (H/V)</b>	140°/125° (Typical)	
	<b>Display Color</b>	16.7M	
	<b>Response Time</b>	8ms (GTG)	
	<b>Frequency (H/V)</b>	H: 30kHz - 60kHz V: 56Hz - 75Hz	
	<b>Max. Pixel Clock</b>	80MHz	
Input	<b>Life Time</b>	50,000hrs (Minimum)	
	<b>Analog</b>	15-Pin D-Sub	
	<b>Digital</b>	24-Pin DVI-D	
	<b>S-Video*</b>	4-Pin Mini Din S-Video	
Connector	<b>CVBS*</b>	CVBS Jack	
	<b>Power</b>	3-Pin AC Plug	
NeoV Optical Glass	<b>Thickness</b>	3.0mm (0.18")	
	<b>Reflection Rate</b>	<1%	
	<b>Transmission Rate</b>	>96%	
	<b>Hardness</b>	>6H (MOH's Rating)	
Tilt	<b>Tilt</b>	0° ~ +20°	
Mounting	<b>VESA FPMPI</b>	Yes (100mm)	
Regulation Approval	<b>Certifications &amp; Compliance</b>	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2,GOST, EPA, WEEE, RoHS	
	<b>VESA</b>	DDC 2B, DPMS	
Power	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz <25W (On) <2W (Stand-by) <1W (Off)	
	Dimensions	<b>Net (W x H x D)</b>	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
		<b>Packing (W x H x D)</b>	445 x 490 x 225mm (17.5" x 19.2" x 8.9")
Weight	<b>Net Weight</b>	4.8Kg (10.6lbs)	
	<b>Gross Weight</b>	7.0Kg (15.4lbs)	
Packing	<b>1 Pallet</b>	40 Cartons	
	<b>20' Container</b>	480 Sets	
	<b>40' Container</b>	1040 Sets	

\*Video inputs are optional functions

All specifications are subject to change without prior notice

