

X-17



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 3ms response time
- High 800 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	800:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	160°/160° (Typical)
	Display Color	16.7M
	Response Time	3ms (GTG)
Input	Frequency (H/V)	H: 30kHz - 80kHz V: 56Hz - 75Hz
	Max. Pixel Clock	135MHz
	Life Time	50,000hrs (Minimum)
	Connector	Power 3-Pin AC Plug
NeoV Optical Glass	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
Thickness	Power	3-Pin AC Plug
	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
Hardness	Hardness	>6H (MOH's Rating)
	Tilt	0° ~ +15°
	Mounting	VESA FPMPI Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2, EPA, GOST, WEEE, RoHS
	VESA	DDC 2B, DPMS
	Power	Power AC Consumption 100 - 240V, 50 - 60Hz <48W (On) <2W (Stand-by) <1W (Off)
Dimensions	Net (W x H x D)	408 x 398 x 175mm (16.1" x 15.7" x 6.9")
	Packing (W x H x D)	495 x 510 x 228mm (19.5" x 20.0" x 9.0")
Weight	Net Weight	6.8Kg (13.9lbs)
	Gross Weight	9.5Kg (20.9lbs)
Packing	1 Pallet	40 Cartons
	20' Container	360 Sets
	40' Container	840 Sets

*Video inputs are optional functions

All specifications are subject to change without prior notice

