

X-19



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 4ms response time
- Crisp 700 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security socket
- VESA standard wall mount
- Available colors: black, white



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	150°/135° (Typical)
	Display Color	16.7M
	Response Time	4ms (GTG)
Frequency (H/V)	H:	30kHz - 80kHz
	V:	50Hz - 75Hz
Max. Pixel Clock		135MHz
	Life Time	50,000hrs (Typical)
Input	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
Connector	Power	3-Pin AC Plug
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	0° ~ +15°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2, EPA, GOST, WEEE, RoHS
		VESA
Power	Power AC Consumption	100 – 240V, 50 – 60Hz
		<48W (On)
		<2W (Stand-by) <1W (Off)
Dimensions	Net (W x H x D)	444 x 419 x 175mm (17.5" x 16.5" x 6.9")
	Packing (W x H x D)	540 x 525 x 228mm (21.2" x 20.7" x 9.0")
Weight	Net Weight	7.9Kg (17.4lbs)
	Gross Weight	10.7Kg (23.6lbs)
Packing	1 Pallet	32 Cartons
	20' Container	320 Sets
	40' Container	704 Sets

*Video inputs are optional functions

All specifications are subject to change without prior notice

