

X-20



▶ FEATURES

- Distinctive aluminum and magnesium alloy housing for added strength
- NeoV Optical Glass™
- Swift 8ms response time
- Super 1000 contrast ratio
- High 300 brightness
- 170° wide viewing angles
- DVI ready for high quality signal
- Multiple video inputs*
- Cable organizer
- Kensington® security socket
- User-friendly OSD



▶ SPECIFICATION

Panel	Panel Type	TFT LCD	
	Panel Size	20.1" (511mm)	
	Max. Resolution	UXGA 1600 x 1200	
	Pixel Pitch	0.255mm	
	Brightness	300cd/m ² (Typical)	
	Contrast Ratio	1000:1 (Typical)	
	Surface Treatments	Hard Coating (2H), Anti-glare Treatment	
	Viewing Angle (H/V)	170°/170° (Typical)	
	Display Color	16.7M	
	Response Time	8ms (GTG)	
	Frequency (H/V)	H: VGA Analog - 30kHz - 94kHz H: VGA DVI - 30kHz - 80kHz V: 50Hz - 75Hz	
	Max. Pixel Clock	Analog: 203MHz, DVI: 165MHz	
	Life Time	50,000hrs (Typical)	
Input	Analog	15-Pin D-Sub	
	Digital	29-Pin DVI-D	
	S-Video*	4-Pin Mini Din S-Video	
	CVBS*	CVBS Jack	
Connector	Power	3-Pin AC Plug	
NeoV Optical Glass	Thickness	3.0mm (0.18")	
	Reflection Rate	<1%	
	Transmission Rate	>96%	
	Hardness	>6H (MOH's Rating)	
Tilt	Tilt	0° ~ +15°	
Mounting	VESA FPMPI	Yes (100mm)	
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/BAURT, CE, BSMI, CB, ISO 13406-2, GOST, WEEE, RoHS	
		VESA	DDC 2B, DPMS
		Power AC Consumption	100 - 240V, 50 - 60Hz <60W (On) <4W (Stand-by) <2W (Off)
Dimensions	Net (W x H x D)	499 x 454 x 180mm (19.7" x 17.9" x 7.1")	
	Packing (W x H x D)	594 x 261 x 570mm (23.4" x 10.3" x 22.4")	
Weight	Net Weight	8.2Kg (18.2lbs)	
	Gross Weight	11.0Kg (24.2lbs)	
Packing	1 Pallet	32 Cartons	
	20' Container	320 Sets	
	40' Container	640 Sets	

*Video inputs are optional functions

All specifications are subject to change without prior notice