



DS 101-IND / DS 101-EMB

RUGGEDIZED DOT MATRIX PRINTER
For industrial or embedded environment

Technical specifications

Printing method

Impact dot matrix
Bidirectionnal printing
9 Pins print head
Print head life : 100 millions characters

Printing speed

Draft mode : 200 cps at 10 cpi, 240 cps at 12 cpi
NLQ mode : 50 cps at 10 cpi, 60 cps at 12 cpi
(Near Letter Quality)
Paper feed speed : 10 lines per second at 6 lpi

Emulations

Epson FX-850
IBM Proprinter II

Fonts

Resident fonts : Courier, Gothic, Sans Serif, Prestige, Script
Standard character set : ASCII, extended, IBM table 1 and 2
Character type : italic, condensed, bold, double strike, double width, double height, superscript, subscript, overlined, underlined

Paper

Tractor or friction feed
Semi-automatic loading of single sheet from the top of the printer.
Paper width : 4.5" to 10 " (8 " printing width)
Multiple copies : 1 original plus 2 copies (non carbon)
Total thickness of less than 0.2 mm
Paper weight : 53 to 81 g/m²

Interfaces

Parallel or serial RS-232C (both installed)

Data buffer

9.3 to 21 kb

Ribbon

Black
2.5 millions of characters

Noise level

Below 57dBa

Power supply

220 V AC +/- 10%, 50 Hz (DS101-IND model)
12 to 24 V DC +/- 10% (DS101-EMB model)

External dimensions

387 (width) x 130 (height) x 263 (depth) mm (DS101-IND model)

Weight

Approximately 7 kg

Color

Grey

Fixing accessories (DS101-EMB)

Shock and anti-vibration holder
for horizontal or vertical mounting

Warranty

-One year warranty excluding printhead



DS 101-IND



DS 101-EMB

ACEL Genesys S.A.S. – ZA – 1, route de Galluis
78940 La-Queue-Lez-Yvelines - FRANCE
Tel. : 33 1 34 86 45 56 – Fax. : 33 1 34 86 42 83
www.acelgenesys.fr